



# Underscore® 5' BubbleMassage™ Bath K-5714-GVBCW



## Features

- Center drain.
- Slotted overflow allows for deep soaking.
- Chromatherapy lighting allows you to select a preferred color scheme to suit your mood.
- Bask® heated surface creates spa-like relaxation with soothing warmth on your back and neck.
- Dual lumbar supports two-person bathing by offering comfort at both ends

## Material

- Acrylic.

## Hydrotherapy

- 118-122 BubbleMassage™ airjets.
- Variable-speed blower for adjusting hydromassage intensity.
- VibrAcoustic® technology emits sound waves and offers a surround sound experience.
- Six concealed speakers send sound waves through the water to gently massage the body.
- Plug in your smart phone, tablet, or MP3 player via auxiliary-in cable. Add your own receiver to stream wirelessly via Bluetooth®.
- Fully adjustable volume above and below the water.
- The BLUETOOTH® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Kohler Co. is under license. Other trademarks and trade names are those of their respective owners.
- Zones of Control™ feature allows you to target massage to back, midsection, or feet.

## Installation

- Drop-in.

## Required Accessories

K-7271 Brass Slotted Overflow Bath Drain

or

K-7272 PVC Slotted Overflow Bath Drain

## Recommended Accessories

K-814 Under-mount Installation Kit



## Codes/Standards











ASME A112.19.7/CSA B45.10  
CSA B45.5/IAPMO Z124  
ASTM E162  
ASTM E662  
UL 1795  
Greenguard UL 2818 - Gold  
CARB P2

## KOHLER® One-Year Limited Warranty

See website for detailed warranty information.

## Available Color/Finishes

*Color tiles intended for reference only.*

Color	Code	Description
	0	White
	96	Biscuit
	47	Almond
	NY	Dune
	95	Ice™ Grey
	G9	Sandbar
	33	Mexican Sand™
	K4	Cashmere
	58	Thunder™ Grey
	7	Black Black™

USA/Canada: 1-800-4KOHLER (1-800-456-4537)


Kohler Co. reserves the right to make revisions without notice to product specifications.

For the most current Specification Sheet, go to [www.kohler.com](http://www.kohler.com).

1-13-2017 05:49

THE BOLD LOOK  
OF **KOHLER**®

No change in measurements if connected with drain illustrated. (K-7272)



### Required Electrical Service

One dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI) or Residual Current Device (RCD).

Amplifier, Heated 120 V, 15 A, 60 Hz  
Surface, Blower:

### Technical Information

All product dimensions are nominal.

Installation: Drop-in, Under-mount  
Drain location: Center  
Basin area, bottom: 43" x 25-5/8" (1093 mm x 651 mm)  
Basin area, top: 55-9/16" x 28-3/8" (1411 mm x 720 mm)  
Weight: 120 lbs (54.4 kg)  
Minimum floor load: 51.2 lbs/ft² (250 kg/m²)  
Water depth: 16-5/16" (415 mm)  
Water capacity: 72.017 gal (272.6 L)  
Template: Drop-in, 1268438-7, required, included  
Electrical component rating:  
Amplifier: 120 V, 1.2 A, 50/60 Hz  
Heated Surface: 120 V, 0.5 A, 60 Hz, 65 W  
Blower: 120 V, 10 A, 60 Hz, 300 W

### Notes

Measure your actual product for rough-in details.

Install this product according to the installation instructions.

The hot water supply should be 70% of the capacity of the bath or greater. Installations will vary.

Provide one grounded electrical outlet within 24" (610 mm) of each component.

Remote blower installation kit is available for relocating the blower.

Do not relocate or alter the PVC tee or coiled flexible tubing connected to the blower. Follow the blower relocation instructions exactly.

Control amplifier fits 16" (406 mm) center studs.

For under-mount installations, kit K-814 is available.