

Features

- Brass construction.
- Brass valve bodies.
- Quarter-turn washerless ceramic disc valves.
- 5" (127 mm) spout reach.
- Less drain.
- 8" (203 mm) rigid connections.
- Standard Water-Guard® aerator.
- Variety of handle style options.
- 2.0 gal/min (7.6 l/min) maximum flow rate [max at 60 psi (4.14 bar)].

Required Accessories

- K-16012-2 Standard Handles for Widespread Base Faucet
or
K-16012-3 Cross Handles for Widespread Base Faucet
or
K-16012-4 Lever Handles for Widespread Base Faucet
or
K-16012-5 Wristblade Handles for Widespread Base Faucet



ADA

Codes/Standards

ASME A112.18.1/CSA B125.1

NSF 61

NSF 372

All applicable US Federal and State material regulations


DOE - Energy Policy Act 1992

ADA

ICC/ANSI A117.1

KOHLER® Faucet Lifetime Limited Warranty

See website for detailed warranty information.



Technical Information

All product dimensions are nominal.

Spout:

Spout reach: 5" (127 mm)

Faucet:

Flow rate: 2 gal/min (7.6 l/min)

Pressure: 60 psi (4.1 bar)

Notes

Install this product according to the installation guide.

ADA compliant when installed to the specific requirements of these regulations.