

Features

- Integral flange.
- Left drain.
- Integral lumbar support.
- Integral apron.
- 54" (1372 mm) x 30-1/4" (768 mm) x 14" (356 mm)

Material

- Cast iron with Safeguard® finish.

Installation

- Alcove

Recommended Accessories

7160-TF

K-1491 Bath/Whirlpool Pillow

K-1601 Bath/Whirlpool Footstop

K-7213 27" Cable Bath Drain

K-7214 27" Cable Bath Drain



ADA

CSA B651

OBC

Codes/Standards

ASME A112.19.1/CSA B45.2

ASTM F462

ASTM F462

ADA

ICC/ANSI A117.1

CSA B651

OBC


KOHLER® Lifetime Limited Warranty for Cast Iron Components

See website for detailed warranty information.

Available Color/Finishes

Color tiles intended for reference only.

Color	Code	Description
	0	White
	96	Biscuit
	47	Almond



Technical Information

All product dimensions are nominal.

Installation: 3-Wall Alcove

Drain location: Left

Basin area, bottom: 37" x 22" (940 mm x 559 mm)

Basin area, top: 48" x 24" (1219 mm x 610 mm)

Weight: 277 lbs (125.6 kg)

Minimum floor load: 49 lbs/ft² (239.2 kg/m²)

Water depth: 8-5/8" (219 mm)

Water capacity: 30 gal (113.6 L)

Minimum flat for door: 2-15/16" (75 mm)

Notes

Measure your actual product for rough-in details.

Install this product according to the installation instructions.

The hot water supply should be 70% of the capacity of the bath or greater. Installations will vary.

ADA, OBC, CSA B651 compliant when installed to the specific requirements of these regulations.