



## Shower Light K-7471-KN

### Features

- Thermally insulated housing with a 12-volt transformer
- 4-5/16" (11 cm) diameter finished trim ring
- 2-3/4" (7 cm) diameter frosted glass dome lens
- Requires MR-16 bulb of 50 watts or less (not included)
- Installs flush with the module ceiling
- Intended for use with Sonata® and Freewill® bath and shower modules
- Light shall be UL listed for wet locations
- 17-7/8" (45.4 cm) x 10-3/4" (27.3 cm) x 7-5/8" (19.4 cm)



### Codes/Standards

UL 1598

CSA C22.2 No. 250

See website for detailed warranty information.

### Available Color/Finishes

*Color tiles intended for reference only.*

Color	Code	Description
	CP	Polished Chrome



## Shower Light K-7471-KN



### Required Electrical Service

One dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI) or Residual Current Device (RCD).

Lights: 120 V, 15 A, 60 Hz

### Technical Information

All product dimensions are nominal.

Electrical component Lights:  
rating:

### Notes

Install this product according to the installation guide.

Do not use a light bulb exceeding 50 watts.

12 V, 50 W, MR-16 bulb required (not included).