



Tea-for-Two®

5.5' Whirlpool Bath

K-856-M

Features

- End drain.
- Integral lumbar support.
- Pre-drilled for grab bars.
- 66" (1676 mm) x 36" (914 mm) x 23" (584 mm)

Material

- Cast iron with Safeguard® finish.

Hydrotherapy

- Six fully adjustable Flexjet™ hydrotherapy jets for water flow and direction.
- Ten sequencing Bodyssage™ backjets.
- Two pulsating neckjets with pillows.
- Built-in 1500 W heater.
- Lighted keypad control.
- Remote control.

Installation

- Drop-in

Required Accessories

K-7148-AF 1-1/2" Contoured Pop-up Drain
K-9653 Grab Bars

Recommended Accessories

K-1601 Bath/Whirlpool Footstop
K-9498 3" Keypad Trim



Codes/Standards











ASME A112.19.1/CSA B45.2
ASME A112.19.7/CSA B45.10
ASTM F462
UL 1795
CSA C22.2 No. 218.2
CARB P2


KOHLER® Lifetime Limited Warranty for Cast Iron Components

See website for detailed warranty information.

Available Color/Finishes

Color tiles intended for reference only.

Color	Code	Description
	0	White
	96	Biscuit
	47	Almond
	NY	Dune
	95	Ice™ Grey
	G9	Sandbar
	33	Mexican Sand™
	K4	Cashmere
	58	Thunder™ Grey
	7	Black Black™



NOTE: Pump/piping protrudes beyond rim.

➤ Pump/Control Access
34" (864 mm) W x
15" (381 mm) H Min

One dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI) or Residual Current Device (RCD).

Cast iron whirlpools are extremely heavy, making some drop-in installations difficult. Splitting the deck/surround is recommended if installing into a deck.