



Memoirs® Memoirs®

60" x 36" Shower Base

K-9489



Features

- Integral flange.
- Left drain.
- Integral seat.
- One-piece construction.
- Coordinates with other products in the Memoirs collection.
- Coordinates with Choreograph™ walls.

Material

- Acrylic
- Reinforced with fiberglass (FRP).

Installation

- Alcove

Required Accessories

K-9132 Shower Drain

Recommended Accessories

1708

K-1733 9 kW Steam Generator

K-702206-G54 Frameless Sliding Shower Door

K-702206-G73 Frameless Sliding Shower Door

K-702206-L Frameless Sliding Shower Door

K-702207-L Frameless Sliding Shower Door

K-702217-L Frameless Sliding Shower Door

K-705705-L Frameless Pivot Shower Door

K-705711-L Frameless Pivot Shower Door

K-705717-L Frameless Pivot Shower Door

K-705723-L Frameless Pivot Shower Door

K-705729-L Frameless Pivot Shower Door

K-705741-L Frameless Pivot Shower Door

K-705810-L Semi-Frameless Pivot Shower Door

K-705811-L Semi-Frameless Pivot Shower Door

K-705824-L Semi-Frameless Pivot Shower Door

K-705825-L Semi-Frameless Pivot Shower Door

K-706009-D3 Frameless Sliding Shower Door

K-706009-L Frameless Sliding Shower Door

K-706013-L Frameless Sliding Shower Door

K-706015-D3 Frameless Sliding Shower Door

K-706015-L Frameless Sliding Shower Door

K-706019-L Frameless Sliding Shower Door



Codes/Standards

ASME A112.19.1/CSA B45.2

CSA B45.5/IAPMO Z124

ASTM E162

ASTM E662

Greenguard UL 2818 - Gold

KOHLER® One-Year Limited Warranty

See website for detailed warranty information.

Available Color/Finishes

Color tiles intended for reference only.

Color	Code	Description
	0	White
	96	Biscuit
	47	Almond
	NY	Dune
	95	Ice™ Grey
	G9	Sandbar
	33	Mexican Sand™
	K4	Cashmere
	58	Thunder™ Grey
	7	Black Black™


USA/Canada: 1-800-4KOHLER (1-800-456-4537)

Kohler Co. reserves the right to make revisions without notice to product specifications.

For the most current Specification Sheet, go to www.kohler.com.

12-20-2016 07:53

THE BOLD LOOK
OF **KOHLER**®



Technical Information

All product dimensions are nominal.

Installation: 3-Wall Alcove

Drain location: Left

Drain hole diameter: 3-3/8" (86 mm)

Weight: 94 lbs (42.6 kg)

Minimum floor load: 21 lbs/ft² (102.5 kg/m²)

Minimum flat for door: 0" (0 mm)

Notes

Measure your actual product for rough-in details.

Install this product according to the installation instructions.

Shimming may be required to level the fixture.

Shimming may be required between the stud frame and the fixture.

Stud opening tolerance is + 1/4" (6 mm), - 0" (0 mm).