

Features

- Two-handle widespread bathroom sink faucet for 8" - 16" centers.
- UltraGlide® valves, featuring advanced ceramic disc technology, improve flow and temperature control, offering consistent lifetime performance.
- Laminar flow delivers a graceful stream while conserving water.
- Constructed with premium materials for durability and reliability.
- Kohler finishes resist corrosion and tarnishing.
- 1.2 gpm (gallons per minute) maximum flow rate.
- Coordinates with other products in the Elliston collection.

Water Conservation & Rebates

- WaterSense®-labeled 1.2-gpm faucets use at least 45 percent less water than standard 2.2-gpm faucets while still meeting strict performance guidelines.



ADA

CSA B651

Codes/Standards

ASME A112.18.1/CSA B125.1

NSF 61

NSF 372

All applicable US Federal and State material regulations

DOE - Energy Policy Act 1992

EPA WaterSense®

California Energy Commission (CEC)

ADA

ICC/ANSI A117.1

CSA B651

See website for detailed warranty information.

Available Color/Finishes


Color tiles intended for reference only.

Color Code Description



CP Polished Chrome

BN Vibrant® Brushed Nickel



Technical Information

All product dimensions are nominal.

Drain included: YES

Drain tailpiece included: YES

Spout:

Spout reach: 4-3/4" (121 mm)

Handle clearance: 2-3/4" (70 mm)

Faucet:

Flow rate: 1.2 gal/min (4.5 l/min)

Pressure: 60 psi (4.1 bar)

Notes

Install this product according to the installation guide.

ADA, CSA B651 compliant when installed to the specific requirements of these regulations.