

### Features

- Metal construction.
- Intended for use with Rite-Temp<sup>®</sup> or HiFlow Rite-Temp<sup>®</sup> valves.
- Sculpted lever handle.
- Includes showerhead with arm and flange, 5-1/4" (133 mm) diverter spout with NPT connection, and faceplate with handle.
- 2.0 gal/min (7.6 l/min) maximum flow rate showerhead with Katalyst™ Spray Technology.

### Required Accessories

K-304/K-P304 Series Rite-Temp<sup>®</sup> Valves

or

K-2971-KS 3/4" Pressure-balancing Valve

### Optional Accessories

GP1025388 Deep Roughing-in Kit for Forte<sup>®</sup> and Bancroft<sup>®</sup>  
88526 Thin Wall Trim Kit



### Codes/Standards

ASME A112.18.1/CSA B125.1

ASSE 1016

DOE - Energy Policy Act 1992

### KOHLER<sup>®</sup> Faucet Lifetime Limited Warranty

See website for detailed warranty information.


### Available Color/Finishes

*Color tiles intended for reference only.*

Color	Code	Description
-------	------	-------------



BN	Vibrant <sup>®</sup> Brushed Nickel
----	-------------------------------------



### Technical Information

All product dimensions are nominal.

#### Spout:

Spout reach: 5-1/4" (133 mm)

Handle clearance: 2-7/8" (73 mm)

#### Showerhead:

Rated maximum flow: 2 gal/min (7.6 l/min)

Pressure: 80 psi (5.5 bar)

### Notes

For use with automatic compensating valves rated at 1.7 gal/min (6.4 l/min) or less.

Install this product according to the installation guide.

**NOTICE:** Risk of product damage. Long screws, for installing trim, can damage the K-2971-KS valve. Consult the trim installation guide to verify if the thin wall installation kit (88526) is needed.

Avoid cross-flow conditions. Do not install shut-off device on either valve outlet.

Install straight pipe or tube drop of 7" (178 mm) to 18" (457 mm) with single elbow between valve and wall-mount spout.