



# Memoirs® | K-1418-JHE

72" x 42" drop-in whirlpool bath

## Features

- Eight Proflex® hydromassage jets can be individually adjusted for water flow and direction
- Built-in heater
- Comfort Depth® design offers a convenient 19" step-over height while retaining the same depth as a standard 21" bath
- Spacious design accommodates up to two bathers
- Integral lumbar support
- Multiple pump location options give you more choices for installation and access
- Coordinates with other products in the Memoirs collection



## Available Colors/Finishes

*Color tiles intended for reference only.*

- |    |         |
|----|---------|
| 0  | White   |
| 96 | Biscuit |



1-800-4KOHLER (1-800-456-4537)  
Kohler Co. reserves the right to make revisions without notice to product specifications.  
For the most current specification sheet, go to [www.kohler.com](http://www.kohler.com) USA or [www.kohler.ca](http://www.kohler.ca) Canada.  
5-30-2026 23:16 - US-CA

THE BOLD LOOK  
OF **KOHLER**®

## Codes/Standards

ASME A112.19.7/CSA B45.10  
CSA B45.5/IAPMO Z124  
ASTM E162  
ASTM E662  
UL 1795  
CSA C22.2 No. 218.2  
cUL Listed  
UL Listed

## Technical Information

*All product dimensions are nominal.*

|                        |                                                |
|------------------------|------------------------------------------------|
| Drain Location:        | Center                                         |
| Drain Hole Diameter:   | 2-1/4" (57 mm)                                 |
| Minimum Flat for Door: | 3-13/16" (97 mm)                               |
| Basin Area, Bottom:    | 48" x 27" (1219 mm x 686 mm)                   |
| Basin Area, Top:       | 60" x 30" (1524 mm x 762 mm)                   |
| Water Depth:           | 16" (406 mm)                                   |
| Water Capacity:        | 94 gal (355.8 L)                               |
| Minimum Floor Load:    | 45 lbs/ft <sup>2</sup>                         |
| Weight:                | 135 lbs (61.2 kg)                              |
| Cutout:                | Drop-in, 70-1/2" x 40-1/2" (1791 mm x 1029 mm) |

## Material

- Acrylic

## Recommended Products/Accessories

K-1491 Bath/whirlpool pillow, removable  
K-1601 Bath/whirlpool footstop, removable

## Required Products/Accessories

- 1015255 Jet Trim Kit
- or
- K-T37392 Rotary-turn bath drain trim
  - K-T37391 Rotary-turn bath drain trim
- or
- K-78439 45" cable bath drain
  - K-37385 Rough-in cable drain, PVC, 45" cable, less horizontal tube

## Technology

- Whirlpool jets recirculate water, providing targeted relief for the bather

## Required Electrical Service

Two dedicated circuits required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI). Outside North America, this device may be known as a Residual Current Device (RCD).

|         |                    |
|---------|--------------------|
| Pump:   | 120 V, 15 A, 60 Hz |
| Heater: | 120 V, 60 Hz       |

## Electrical Component Ratings

|         |                    |
|---------|--------------------|
| Pump:   | 120 V, 7 A, 60 Hz  |
| Heater: | 120 V, 12 A, 60 Hz |


## Warranty

*See website for detailed warranty information.*

KOHLER® Plastic Baths and Shower Bases Lifetime Limited Warranty|KOHLER® Hydrotherapy Components Five-Year Limited Warranty



No change in measurements if connected with drain illustrated. (K-7161-AF)



## Installation

- Drop-in
- Rear center drain

## Installation Notes

*Install this product according to the installation instructions.*

Measure your actual product for rough-in details.

The hot water supply should be 70% of the capacity of the bath or greater. Installations will vary.

