



Tresham® | K-1977

60" x 32" alcove shower base, left drain

Features

- Low-threshold design for easy entry and exit
- Single threshold for three-wall installation
- Durable plastic construction
- Integral 18" (457 mm) undercut seat at right
- Coordinates with other products in the Tresham collection



Available Colors/Finishes

Color tiles intended for reference only.

0 White



1-800-4KOHLER (1-800-456-4537)
Kohler Co. reserves the right to make revisions without notice to product specifications.
For the most current specification sheet, go to www.kohler.com USA or www.kohler.ca Canada.
5-31-2026 0:8 - US-CA

THE BOLD LOOK
OF **KOHLER**

Codes/Standards

CSA B45.5/IAPMO Z124
ASTM E162
ASTM E662

Technical Information

All product dimensions are nominal.

Drain Location:	Left
Drain Hole Diameter:	3-3/8" (86 mm)
Shower Ledge Minimum Flat:	2-1/2" (64 mm)
Minimum Floor Load:	20 lbs/ft ²
Weight:	72 lbs (32.7 kg)

Material

- Acrylic

Recommended Products/Accessories

K-23726 Drain treatment
K-23732 Tub & shower cleaner
K-706009-D3 56-5/8"-59-5/8" W x 74" H bypass shower door with 1/4"-thick Frosted glass
K-706009-L 56-5/8"-59-5/8" W x 74" H bypass shower door with 1/4"-thick Crystal Clear glass
K-706015-D3 56-5/8"-59-5/8" W x 74" H bypass shower door with 1/4"-thick Frosted glass
K-706015-L 56-5/8"-59-5/8" W x 74" H bypass shower door with 1/4"-thick Crystal Clear glass
K-9132 Round shower drain for use with plastic pipe, gasket included


Warranty

See website for detailed warranty information.

KOHLER® Plastic Baths and Shower Bases Lifetime Limited Warranty



1-800-4KOHLER (1-800-456-4537)
Kohler Co. reserves the right to make revisions without notice to product specifications.
For the most current specification sheet, go to www.kohler.com USA or www.kohler.ca Canada.
5-31-2026 0:8 - US-CA



Installation

- Left drain

Installation Notes

Install this product according to the installation instructions.

Measure your actual product for rough-in details.

Shimming may be required between the stud frame and the fixture.

Stud opening tolerance is +1/4" (6 mm), -0" (0 mm).

KOHLER steam generator/control kit are designed for use with this product. Kohler Co. shall not be responsible for problems encountered due to the installation and use of other manufacturer's steam generators.

