## **KWC DOMO**





9 13/16" 5 1/4"

14 3/8"

110°

2 9/16"

M33

22 1/16"

3/8"comp.

KWC-No.

**Finish** 

**10.061.004.127** 9 <sup>13</sup>/<sub>16</sub>" spout length **10.061.004.000**  splendure™ stainless steel

chrome

9 13/16" spout length

## Kitchen Pull-Down Faucet with flexguard™

Single-lever mixer

• lever installation right side only

Child safety: cold water flow in lever position towards the front flexguard™ - Sealing membrane between lever and cap:

- protects the inside of the faucet
- to prevent liquid penetrating from outside

Space between wall and mounting hole minimum of 1"

Pull-out spray - magnetic tight-fit holder

• ergonomic shape and spout alignment for ease of handling

KWC jetclean<sup>™</sup> technology

- Caché® hidden aerator
- automatic diverter reset
- pull-out length up to 23 5/8"
- hose surface to fit faucet surface
- hose guide secures hose back in place
- swivel range 360°

KWC L 39 control cartridge

- ceramic discs
- variable flow rate and temperature
- temperature and flow rate limitation

Flexible connection hoses 3/8" compression

M33 x 1.5 threaded sleeve fastening

Mounting hole size ø1 3/8"

Flow rate max 1.75 gpm (60 psi) Flow rate needle spray max 1.75 gpm (60 psi) Acoustic group I