

Buy it for looks. Buy it for life.®

There is more than 1 version of this model. Page down to identify the version you have.

FAUCET DESCRIPTION

- Versatile, hands-free convenience in the kitchen
- Allows users to control the faucet in 3 unique ways: Wave Sensor, Ready Sensor and familiar handle Powered by 6 AA batteries or optional AC power adapter
- Reflex™ pulldown system offers smooth operation, easy movement and secure docking
- Metal construction with various finishes identified by suffix Hydrolock® quick connect installation
- Pulldown spray with 68" braided hose
- Valve flexible supply lines with 3/8" compression fittings Spout uses push-fit hose connections
- High arc spout provides height and reach to fill or clean large pots while pull down wand provides the maneuverability for cleaning or rinsing

Includes liquid soap dispenser OPERATION

- Lever style handle
- Temperature controlled by 100° arc of handle travel Operates with less than 5 lbs. of force
- Operates in stream or spray mode in the pulldown or retracted position
- Spout rotates 100 degrees
- When filling a vessel outside the sink, the pause feature conveniently stops the flow of water as the wand passes over the counter top

Flow is limited to 1.5 gpm (5.7 L/min) at 60 psi CARTRIDGE

Wave

Ready

10-1/4" x 2-3/8"

ESCUTCHEON

46" (1168mm)

6-1/2" (165mm)

30-11/16"

(779mm)

32-3/4" (832mm) 0

Duralast™ cartridge for Single-Handle Faucets

STANDARDS

- Third party certified to ASME A112.18.1/CSA B125.1 and all applicable requirements referenced therein including NSF 61/9 Meets Georgia SB370 requirements
- Complies with California Proposition 65 and with the Federal Safe Drinking Water Act
- The backflow protection system in the device consists of two independently operating check valves, a primary and a secondary which prevent backflow
- ADA (for lever handle

WARRANTY

Limited lifetime warranty against leaks, drips, finish defects to the original consumer purchaser 5 year warranty electronic operation defects to the original consumer purchaser

_ 4-7/8" (124mm)

1/2"

(76mm)

4-1/2"— (114mm)

- year warranty against leaks, drips, finish defects if used in commercial installations
- 1 year warranty against electronic operation defects if used in commercial installations

Specifications



MotionSense™ Single Handle High Arc **Pulldown Kitchen Faucet**


Models: 87359E SERIES

NOTE: THIS FAUCET IS DESIGNED TO BE INSTALLED THRU 1 OR 3 HOLES, 1-1/2" (38mm) MIN. DIA.






Close up view of Control Box



Battery Holder





AC Power Adapter (sold separately) 163712

36" Cord (914mm)

8-1/4"

2-1/2"

7-7/8" (199mm)

TO ORDER PARTS CALL: 1-800-BUY-MOEN

www.moen.com



Buy it for looks. Buy it for life.®

FAUCET DESCRIPTION

- Versatile, hands-free convenience in the kitchen
- Allows users to control the faucet in 3 unique ways: Wave Sensor, Ready Sensor and familiar handle Powered by 6 AA batteries or optional AC power adapter
- Reflex™ pulldown system offers smooth operation, easy movement and secure docking
- Metal construction with various finishes identified by suffix
- Hydrolock® quick connect installation
- Pulldown spray with 68" braided hose Valve flexible supply lines with 3/8" compression fittings
- Spout uses push-fit hose connections
- High arc spout provides height and reach to fill or clean large
- pots while pull down wand provides the maneuverability for cleaning or rinsing

Includes liquid soap dispenser

- Temperature controlled by 100° arc of handle travel
- Operates with less than 5 lbs. of force
- Operates in stream or spray mode in the pulldown or retracted position
- Spout rotates 100 degrees
- When filling a vessel outside the sink, the pause feature conveniently stops the flow of water as the wand passes over the counter top

Flow is limited to 1.5 gpm (7.6 L/min) at 60 psi

Wave Sensor

> Ready Sensór

10-1/4" x 2-3/8"

(260mm x 60mm) ESCUTCHEON

(165mm)

30-11/16" (779mm)

32-3/4" (832mm)

CARTRIDGE

Duralast™ cartridge for Single-Handle Faucets

STANDARDS

- Third party certified to ASME A112.18.1/CSA B125.1 and all applicable requirements referenced therein including NSF 61/9
- Meets Georgia SB370 requirements
- Complies with California Proposition 65 and with the Federal Safe Drinking Water Act
- The backflow protection system in the device consists of two independently operating check valves, a primary and a secondary which prevent backflow
- ADA (for lever handle

WARRANTY

Limited lifetime warranty against leaks, drips, finish defects to the original consumer purchaser

15-1/2" 4-7/8" (394mm)

8-1/4"

(210mm)

2-1/2" (64mm) Max Deck Thickness

(124mm)

(13mm)

(76mm)

4-1/2"-(114mm)

- 5 year warranty electronic operation defects to the original consumer purchaser
- year warranty against leaks, drips, finish defects if used in commercial installations
- 1 year warranty against electronic operation defects if used in commercial installations

Specifications



MotionSense™ **Single Handle High Arc Pulldown Kitchen Faucet**

Models: 87359E SERIES


NOTE: THIS FAUCET IS DESIGNED TO BE INSTALLED THRU 1 OR 3 HOLES, 1-1/2" (38mm) MIN. DIA.




7-7/8" (199mm)



Close up view of Control Box



Battery Holder



CRITICAL DIMENSIONS (DO NOT SCALE)

AC Power Adapter

(sold separately) 163712 36" Cord (914mm)

TO ORDER PARTS CALL: 1-800-BUY-MOEN

www.moen.com