



MODA™ ICE MAKER SUPPLY BOX

Job Name:	Item #:
Location:	
Engineer:	Contractor:
PO#:	Tag:
Representative:	

SPECIFICATION

Oatey MODA™ ice maker supply boxes shall be used in residential or commercial applications requiring a supply valve recessed in the wall. The MODA™ ice maker box assembly contains a 1/4" OD compression valve pre-installed in a PVC box, with inter-locking wing flanges on each side. The wing flanges shall allow installation on a single stud, or between two studs using the included side brackets. No additional components shall be required for a between stud installation. Valves shall be a two-piece design, permitting field replacement, and shall be secured with a stainless steel retention clip. Valves are available with or without water hammer arrestors and shall be installed upright or inverted. The assembly shall include an emergency drain port for protection from tubing leaks.

MATERIALS

Outlet Box & Brackets	PVC
Valve Body	Forged Brass C46500 No Lead
Valve Retention Clip	Stainless Steel
Valve O-Rings	NSF Approved EPDM (2)

PERFORMANCE SPECIFICATIONS

Temperature Rating (Valve)	250° F / 121° C
Max Testing Pressure (Valve)	100 psi (Air) / 250 psi (Water)

LISTINGS & CODE APPROVALS

Valves	ASME A112.18.1 / CSA B125.1 NSF / ANSI 61 & 372
Water Hammer Arrestors	ASSE 1010
Boxes	IAPMO-Listed, PS-54



DIMENSIONS

[A]: Box Width	8.00"	[E]: Bracket Length	8.00"
[B]: Box Depth	3.38"	[F]: Faceplate Width	6.00"
[C]: Box Height	4.85"	[G]: Faceplate Height	6.45"
[D]: Bracket Width	4.00"	[H]: Faceplate Depth	1.25"

PRODUCT SELECTOR

No Hammer Arrestors				Hammer Arrestors			
☐ 37679	IMOB, Copper, NoHam, Std Pk	☐ 37695	IMOB, Copper, NoHam, Cont Pk	☐ 37687	IMOB, Copper, Ham, Std Pk	☐ 37703	IMOB, Copper, Ham, Cont Pk
☐ 37681	IMOB, F1807-Brass, NoHam, Std Pk	☐ 37697	IMOB, F1807-Brass, NoHam, Cont Pk	☐ 37689	IMOB, F1807-Brass, Ham, Std Pk	☐ 37705	IMOB, F1807-Brass, Ham, Cont Pk
☐ 37682	IMOB, F2159-PPSU, NoHam, Std Pk	☐ 37698	IMOB, F2159-PPSU, NoHam, Cont Pk	☐ 37690	IMOB, F2159-PPSU, Ham, Std Pk	☐ 37706	IMOB, F2159-PPSU, Ham, Cont Pk
☐ 37683	IMOB, F1960-Brass, NoHam, Std Pk	☐ 37699	IMOB, F1960-Brass, NoHam, Cont Pk	☐ 37691	IMOB, F1960-Brass, Ham, Std Pk	☐ 37707	IMOB, F1960-Brass, Ham, Cont Pk
☐ 37684	IMOB, F1960-PPSU, NoHam, Std Pk	☐ 37700	IMOB, F1960-PPSU, NoHam, Cont Pk	☐ 37692	IMOB, F1960-PPSU, Ham, Std Pk	☐ 37708	IMOB, F1960-PPSU, Ham, Cont Pk
☐ 37680	IMOB, CPVC, NoHam, Std Pk	☐ 37696	IMOB, CPVC, NoHam, Cont Pk	☐ 37688	IMOB, CPVC, Ham, Std Pk	☐ 37704	IMOB, CPVC, Ham, Cont Pk
☐ 37686	IMOB, Push Cnc, NoHam, Std Pk			☐ 37694	IMOB, Push Cnc, Ham, Std Pk		

- Standard packs shipped with faceplates on boxes, contractor packs ship with faceplates packaged separately.
- All products sold in case packs of 12.



Accessory Components Included:



Side Brackets (2)



Faceplate



Sticker Cover
(For Debris Protection)



Test Plug



LocPin™
Stainless Steel Retention Clip

