

United Elchem Industries

Turf-Tite™ PVC Cement



MAXIMIZE YOUR PRODUCTIVITY WITH TURF-TITE HOT BLUE CEMENT!

If you assemble irrigation and sprinkler systems, count on Turf-Tite to help you do the job right the first time.

Set Up Time

30°F to 50°F 4-5 minutes

50°F to 70°F 3-4 minutes

70°F to 100°F 1-2 minutes

FAST...

TURF-TITE cement sets up fast

- > Sets up in just 1-2 minutes (see chart)
- > Bond strengths in excess of 250 psi in 10 minutes under lab conditions

EASY...

Versatile cement used in many applications

- > Recommended for use on all schedules and classes of flexible and rigid PVC pipe and fittings up to 6" with interference fit
- > No primer needed on non-pressure DWV up to 4" where local codes permit

System may be hydrostatically tested up to 75 PSI after 15 minutes and up to 180 PSI after 30 minutes.*

*At temperatures above 60°F and up to 2" pipe diameter.

United Elchem Industries

©2011 Oatey SCS. All Rights Reserved.
This information is based on data believed to be reliable but Oatey makes no warranties, express or implied, as to its accuracy and assumes no liability arising out of its use. The data listed falls within the normal range of product properties but should not be used to establish specification limits or used alone as the basis of design. Oatey's liability to purchasers is expressly limited to the terms and conditions of sale.
Oatey is a trademark of Oatey Co. All other trademarks can be found on www.oatey.com.

DISTRIBUTED BY:

OATEYSCS®
Supply Chain Services

216.267.7100 / 800.321.9532
www.oateyscs.com