

ARCHITECTURAL SPECIFICATIONS
PANASONIC ADVANCED VENTILATION SERIES



FV-10VSL3E WhisperValue™ – Ceiling or Wall Mount Fan/Light – 100 CFM

Ventilation fan and light shall be ceiling or wall mount, ENERGY STAR® certified, with no less than 100 CFM and no more than 1.0 sones as certified by the Home Ventilating Institute (HVI) at 0.1 wg with no less than 88 CFM and no more than 1.1 sones at .25 wg. Power consumption shall be no greater than 27.3 Watts at 0.1 wg and 27.0 Watts at 0.25 wg with efficiency of no less than 3.7 CFM/Watt at 0.1 wg and 3.3 CFM/Watt at 0.25 wg. The motor shall be fully enclosed, four pole condenser type engineered to operate continuously for no less than 30,000 hours. Power rating shall be 120v/60Hz. Duct diameter shall be no less than 4" duct. Optional 24 gauge steel, fire code rated 4" oval to 3" round duct adaptor sold separately (Model # FV-VS43R). Fan shall be UL and cUL listed for ceiling or wall mount and tub/shower enclosure when GFCI protected. Fan can be used to comply with ASHRAE 62.2, LEED, EarthCraft, California Title-24 and WA Ventilation Code. Lamps shall be of the compact fluorescent type and utilize no less than two 13 Watt, ENERGY STAR® rated, self-ballasted GU24 base compact fluorescent lamps. Nightlight feature shall be included.