

## ARCHITECTURAL SPECIFICATIONS PANASONIC ADVANCED VENTILATION SERIES



### CEILING MOUNTED 50 CFM VENTILATION FAN

**FV-05VQ5 WhisperCeiling** Ventilating fan shall be of the ceiling mount, ENERGY STAR rated type, with no less than 50 CFM and no more than less than <0.3 sone as certified by the Home Ventilating Institute (HVI) at 0.1 static pressure in inches water gauge (w.g.) with no less than 36 CFM and no more than 0.5 sone as certified by HVI at 0.25 w.g. Power Consumption shall be no greater than 11 watts at 0.1 w.g. and 11.5 watts at 0.25 w.g. ENERGY STAR rated with efficiency of no less than 4.7 CFM/watt at 0.1 w.g. and 3.2 CFM/watt at 0.25 w.g. The motor shall be totally enclosed, four pole condenser type engineered to operate continuously. Power rating shall be 120v/60Hz. Included is a detachable dual 4" or 6" diameter duct adaptor. Duct diameter shall be no less than 4". Fan shall be UL and cUL listed for tub/shower enclosure when used with GFCI branch circuit wiring. Fan shall be ASHRAE 62.2, LEED, ENERGY STAR IAP, EarthCraft, California Title-24, and WA Ventilation Code compliant.