

**ARCHITECTURAL SPECIFICATIONS
PANASONIC ADVANCED VENTILATION SERIES**



CEILING OR WALL MOUNTED VENTILATION FANS WITH LIGHT

FV-08VSL3 WhisperValue Lite – 80 CFM Fan/Light, Ceiling/Wall Mount

Ventilation fan and light shall be ceiling or wall mount, ENERGY STAR® rated, with no less than 80 CFM and no more than 1.0 sones as certified by the Home Ventilating Institute (HVI) at 0.1 wg with no less than 72 CFM and no more than 1.2 sones at .25 wg. Power consumption shall be no greater than 22.5 Watts at 0.1 wg and 22.9 Watts at 0.25 wg with efficiency of no less than 3.6 CFM/Watt at 0.1 wg and 3.1 CFM/Watt at 0.25 wg. The motor shall be fully enclosed, four pole condenser type engineered to operate continuously for no less than 30,000 hours. Power rating shall be 120v/60Hz. Duct diameter shall be no less than or 4". Optional 24 gauge steel, fire code rated 4" oval to 3" round duct adaptor sold separately (Model # FV-VS43R). Fan shall be UL and cUL listed for ceiling or wall installation and tub/shower enclosure when used with a GFCI protected circuit. Fan can be used to comply with ASHRAE 62.2, LEED, ENERGY STAR IAP, EarthCraft, California Title-24 and WA Ventilation Code. Lamps shall be of the compact fluorescent type and utilize no less than two 13 Watt, ESTAR rated, self-ballasted GU24 base compact fluorescent lamps. Night-light feature shall be included.