

**ARCHITECTURAL SPECIFICATIONS
PANASONIC ADVANCED VENTILATION SERIES**



CEILING MOUNTED VENTILATION FANS WITH LIGHT

FV-11VQL6 WhisperLite – 110 CFM Fan/Light, Ceiling Mount

Ventilation fan and light shall be of the ceiling mount, ENERGY STAR rated type, with no less than 110 CFM and no more than 0.5 sone as certified by the Home Ventilating Institute (HVI) at 0.1 static pressure in inches water gauge(w.g.) with no less than 90 CFM and no more than 0.6 sone as certified by HVI at .25 w.g. Power Consumption shall be no greater than 23.4 watts at 0.1 w.g and 23.0 watts at 0.25 w.g. ENERGY STAR rated efficiency of no less than 4.7 CFM/watt at 0.1 w.g. and 3.9 CFM/watt at 0.25 w.g. The motor shall be totally enclosed, four pole condenser type engineered to operate continuously. Power rating shall be 120v/60Hz. Included is an integrated dual 4" or 6" diameter duct adaptor. Duct diameter shall be no less than 4". Fan shall be UL and cUL listed for tub/shower enclosure when used with a GFCI protected circuit. Fan may be used to comply with ASHRAE 62.2, LEED, ENERGY STAR IAP, EarthCraft, California Title-24 and WA Ventilation Code. Lamps shall be of the compact fluorescent type and utilize no less than two 13 Watt ESTAR rated, self-ballasted GU24 base compact fluorescent lamps. Night-light feature shall be included.