

EP Branch Multi-port Elbow

Submittal Information

Revision A: March 6, 2008

Project Information

Job Name:

Location:

Part No. Ordered:

Engineer:

Date Submitted:

Contractor:

Submitted By:

Manufacturer's Representative:

Approved By:

Technical Data

Material:	UDEL GF120
Maximum Temperature (no pressure):	320°F (160°C)
Maximum Working Temperature/Pressure:	210°F (99°C) at 150 psi



Product Information and Application Use

EP Branch Multi-port Elbow features an integrated 3/4" or 1" ProPEX® elbow inlet with 1/2" ProPEX branch outlets.¹ The elbow is designed for commercial plumbing applications, and eliminates the need for multiple connections. The elbow is made of EP, which is proven in demanding hot-water applications.

✓ Description	Part Number	Length	Height	Width	Weight
3/4" EP Branch Multi-port Elbow, 7 outlets	Q2077550	9.00"	2.33"	1.77"	0.350 lbs.
3/4" EP Branch Multi-port Elbow, 8 outlets	Q2087550	9.80"	2.33"	1.77"	0.390 lbs.
1" EP Branch Multi-port Elbow, 10 outlets	Q2101000	11.75"	2.56"	1.77"	0.470 lbs.

Installation

Any product designed to mount 1 1/4" copper pipe (for the EP Branch Multi-port Elbow) may be used as a mounting bracket. For more information, refer to the AQUAPEX® Professional Plumbing Installation Handbook.

Standards

CAN/CSA B137.5; ASTM F877; ASTM F1960

Codes

IPC; UPC; NSPC; NPC of Canada

Listings

ANSI/NSF 14- and 61-certified; ICC ESR 1099; IAPMO 3946

Related Applications

PEX-a Plumbing Systems

Contact Information

Uponor, Inc.
5925 148th Street West
Apple Valley, MN 55124 USA
Phone: (800) 321-4739
Fax: (952) 891-2008
www.uponor-usa.com

Uponor Ltd.
655 Park Street
Regina, SK S4N 5N1 CANADA
Phone: (888) 994-7726
Fax: (800) 638-9517
www.uponor.ca

¹ProPEX® is a registered trademark of Uponor, Inc. ProPEX™ is a trademark of Uponor Ltd.