For Residential and Commercial Applications			
Job Name		Engineer / Architect	
Job Location		Wholesaler	
Submittal Date		Contractor	

BRPX04 / BRPX14 / BRPX34 Multi-Turn Straight Stop – Barbed PEX x Compression

Use: For use with water in accessible locations only. Not intended for recirculating water systems that produce continuous use temperatures above 115° F. For those applications, use our KT[™] series ball stop.

Design Features:

- Machined one-piece brass body provides strength, durability, and long-lasting performance
- Knurled oval handle provides a secure grip and smooth on/off operation
- Easy-to-remove handle with screw attachment helps protect against accidental stop operation during rough-ins
 - **Ø** 1

No Lead

- PEX end designed to ASTM F1807
- For use with ASTM F876 PEX tubing, in ASTM F877 water distribution systems using ASTM F1807, and/or F2098 connection methods



Operating Specifications:

Temperature: 40°- 140° F *Pressure:* 125 PSI maximum

Standard

STOP MATERIAL SPECIFICATIONS		
Body	Brass or brass, chrome plated	
Stem	Brass or brass, chrome plated	
Bib & Packing Washer	Rubber	
Packing Nut	Brass or brass, chrome plated	
Handle	Polycarbonate	
Handle Screw	Zinc-plated steel	
Plastic Sleeve	Delrin	
Compression Nut	Brass, chrome plated	
Compression Sleeve	Brass	

No Lead

STOP MATERIAL SPECIFICATIONS		
Podu	No-Lead brass or No-Lead	
Body	brass, chrome plated	
Stem	No-Lead brass or No-Lead	
Stelli	brass, chrome plated	
Bib & Packing Washer	Rubber	
Packing Nut	Brass or brass, chrome plated	
Handle	Polycarbonate	
Handle Screw	Zinc-plated steel	
Plastic Sleeve	Delrin	
Compression Nut	Brass, chrome plated	
Compression Sleeve	Brass	

Standard Part Listing:

Ш	BRPX04 C	1/2" nom barb (for PEX) x 1/4" OD compression, chrome plated
	BRPX04 R	1/2" nom barb (for PEX) x 1/4" OD compression, rough brass
	BRPX14 C	1/2" nom barb (for PEX) x 3/8" OD compression, chrome plated
	BRPX14 C1	1/2" nom barb (for PEX) x 3/8" OD compression, chrome plated, window tray
	BRPX14 R	1/2" nom barb (for PEX) x 3/8" OD compression, rough brass

This specification and all information contained herein is the confidential and exclusive property of BrassCraft Manufacturing, and shall not be disclosed to others without the written consent of BrassCraft Mfg. This specification must be returned to BrassCraft Mfg. if requested.




BRPX04 / BRPX14 / BRPX34 Multi-Turn Straight Stop – Barbed PEX x Compression

Standard Part Listing Con't:

	BRPX34 C	1/2" nom barb (for PEX) x 1/2" OD compression, chrome plated
	BRPX34 R	1/2" nom barb (for PEX) x 1/2" OD compression, rough brass
No-L	ead Part Listing:	
	BRPX04X C	1/2" nom barb (for PEX) x 1/4" OD compression, chrome plated
	BRPX04X R	1/2" nom barb (for PEX) x 1/4" OD compression, rough brass
	BRPX14X C	1/2" nom barb (for PEX) x 3/8" OD compression, chrome plated
	BRPX14X R	1/2" nom barb (for PEX) x 3/8" OD compression, rough brass

PART DIMENSIONS (Inches)				
Model	DIM. A	DIM. B		
BRPX04	1.67	2.19		
BRPX14	1.67	2.19		
BRPX34	1.67	2.28		



Listings & Certifications:

- IAPMO listed to ASME A112.18.1 / CSA B125.1 (File # 0645)
- CSA listed to ASME A112.18.1 / CSA B125.1 (File # 204593)
- No-Lead product CSA listed to Low Lead Content
 Certification Program Plumbing Products Class 6853-01









