

Pre-insulated Uponor AquaPEX® (ASHRAE 90.1-2013)

Submittal Information

Revision A: June 19, 2015

Project Information

Job Name:	
Location:	Part No. Ordered:
Engineer:	Date Submitted:
Contractor:	Submitted By:
Manufacturer's Representative:	Approved By:

Technical Data

Service Pipe:	Crosslinked polyethylene PEX-a Engel method pipe encased in polyethylene-foam insulation; PEX 5106
Insulation:	Polyethylene foam
Thermal Conductivity:	0.25 Btu.in/sq.ft.h.degF
Operating Condition Limits:	200°F (93°C) at 80 psi (551 kPa) 180°F (82°C) at 100 psi (689 kPa) 73.4°F (23°C) at 160 psi (1,103 kPa) ½"-2" Uponor AquaPEX® White only: 120°F (49°C) at 130 psi (896 kPa)
Linear Expansion Rate:	1.10"/10°F/100' (27.94mm/5.56°C/30.48m)



Product Information and Application Use

Pre-insulated Uponor AquaPEX® (ASHRAE 90.1-2013) features flexible PEX pipe encased in polyethylene-foam insulation to insulate potable-water lines and meet ASHRAE 90.1-2013 energy-code requirements. The product is approved for use in hot and cold domestic potable water systems, residential fire safety and hydronic heating and cooling systems containing no ferrous corrodible components or where ferrous components are isolated from the piping. The product is also approved for direct burial in soil provided it is not exposed to groundwater. Uponor recommends adding ½" of insulation to accommodate for foam compression in direct-burial applications.

✓ Description	Part Number	O.D.	Heat Loss (at 70° Delta T)	R-Value	Coil Size (O.D. x Width)	Weight (lb./coil)
½" Pre-insulated Uponor AquaPEX with 1" insulation, 100-ft.	F6150500	2.59"	6.3 BTU/hr/ft	7.5	45" x 9"	11.0 lbs.
¾" Pre-insulated Uponor AquaPEX with 1" insulation, 100-ft.	F6150750	3.08"	7.1 BTU/hr/ft	7.9	43" x 13.5"	22.0 lbs.
1" Pre-insulated AquaPEX with 1" insulation, 100-ft. coil	F6151000	3.09"	8.8 BTU/hr/ft	6.4	45" x 13.5"	30.2 lbs.
1¼" Pre-insulated AquaPEX with 1" insulation, 100-ft. coil	F6151250	3.34"	10.0 BTU/hr/ft	6.1	52" x 9"	39.2 lbs.
1½" Pre-insulated AquaPEX with 1½" insulation, 75-ft. coil	F6161500	4.93"	7.0 BTU/hr/ft	11.2	54" x 13.5"	49.5 lbs.
2" Pre-insulated AquaPEX with 1½" insulation, 75-ft. coil	F6162000	5.27"	8.6 BTU/hr/ft	9.9	58" x 13.5"	74.3 lbs.

Installation

Approved fitting system is ProPEX®.¹ Refer to the Uponor AquaPEX Professional Plumbing Installation Guide, AquaSAFE™ Residential Fire Sprinkler Installation Guide or Uponor Radiant Installation Handbook for additional information.

Listings²

cNSFus-fs³; cNSFus-pw; cQAIus⁵; UL; CSA; WH⁵; ETL⁵; PPI TR-4; ICC-ES; IAPMO; BMEC; CCMC

Codes

ICC; IPC; IMC; IRC; UPC; UMC; NSPC; HUD; UFGS; NPC of Canada; NBC of Canada

Standards

ANSI/NSF 14; ANSI/NSF 61; ASTM F876; ASTM F877; ASTM F1960; ASTM F2023; ASTM E119/UL 263; CAN/ULC S101; ASTM E814/ULC S115; AWWA C904⁴; CSA B137.5; CSA B214; UL 1821³; ULC/ORD-C199P³

Related Applications

Uponor Plumbing Systems
AquaSAFE Fire Safety Systems
Radiant Heating and Cooling Systems
Hydronic Piping Systems

Contact Information

Uponor, Inc.
5925 148th Street West
Apple Valley, MN 55124 USA
Phone: 800.321.4739
Fax: 952.891.2008
www.uponorpro.com
www.uponorengineering.com

Uponor Ltd.
2000 Argentia Rd., Plaza 1, Ste. 200
Mississauga, ON L5N 1W1 CANADA
Phone: 888.994.7726
Fax: 800.638.9517
www.uponorpro.com
www.uponorengineering.com

¹ProPEX® is a registered trademark of Uponor, Inc. ProPEX™ is a trademark of Uponor Ltd.; ²Visit listing agency's website for complete information; ³For ½", ¾", 1", 1¼", 1½" and 2" pipe only; ⁴For ¾" pipe and larger; ⁵See listings/standards for un-insulated Uponor AquaPEX.