

OLIVIA Bypass Shower Door SMOBPT-

FEATURES


- · An attractive, frameless smooth sliding Bypass shower door that features a special Nano Protected surface treatment that keeps glass looking clean.
- New TruMotion technology features premium engineered rolling mechanism system for easy gliding and quiet sliding door.
- Optional side wall profiles give up to 1" out-of-plumb adjustment on each side or 2" total.
- Walk-in opening: 20-5/8" to 22-1/4" for 48" width door and 26-5/8" to 28-1/4" for 60" width door.
- · Clearance height: 57-7/8" for 62" height door and 75-7/8" for 80" height door.
- · Tempered glass is ANSI Z97.1. certified.
- · Glass thickness: 5/16" (8mm) available in Clear.
- · Exposed zinc alloy rollers with soft-close features and zinc alloy wall bracket. Frame is made from 304 stainless steel with top track having an internal aluminum support.
- Hardware finishes: Polished Chrome, Brushed Stainless, Champagne Bronze, and Matte Black.
- Shower base threshold minimum requirement is 3-3/8" wide.
- Doors come with a pair of 19-5/8" (500mm) Royston bypass handles.
- · Easy to install.
- IMPORTANT! All measurements should be taken only AFTER walls are finished (tile, back walls, etc.); Professional installation recommended.
- · Limited Lifetime Warranty for residential and 1 year for commercial.



Specify Model

Size	Model	Glass	Width	Height	Weight (lbs)
48X80	SMOBPT488008C-	Clear (8 mm)	48"	80"	85
60X62	SMOBPT606208C-	Clear (8 mm)	60"	62"	95
60X80	SMOBPT608008C-	Clear (8 mm)	60"	80"	120

To Be Specified: Hardware Color









1563mm [61-1/2"] - 2020mm [79-1/2"]



Champagne **Bronze**

Matte Black

To Be Specified: Glass





