

Trimslate

Base with Adjustable Double Threshold SMFZSDT End Drain

Features


- Heavy Duty SMC Sheet Molding Compound Material
- Trimslate shower bases with our unique adjustable depth threshold.
- Maximum depth and width can be adjusted by up to 2-1/2" without any trimming of the base.
- Trimslate bases can also be customized in the field to fit your space. Trim up to 4" in width from side opposite drain or up to 2" in depth away from drain.
- Each base is supplied with two 80" long add on trimmable thresholds with a 45-degree mitered edge.
- The threshold has a 4" wide flat surface to accommodate shower doors.
- SMC color-matched drain cover conceals a conventional 2" shower drain (not supplied).
- · The slate floor has a lightly textured and slip-resistant surface that makes it safe, yet remains easy to clean.
- 13-3/4" center drain location for SMFZSDT models.
- 8-1/2" center drain location for SMFZSDTR models. Bases are designed to replace bathtub as drain position will align with existing bathtub drain.
- 1" high aluminum tiling flange included.
- 10 Year Limited Residential / 3 Year Commercial Warranty





Stock Sized Specified Models

Model No.	Min Length A	Max Length A	Min Width B	Max Width B	Height
SMFZSDT6736	68"	70.5"	36.5"	39"	2.75"
SMFZSDT7236	71.9"	74.4"	36.5"	39"	2.75"
SMFZSDTR6032	60.1"	62.6"	32.5"	35"	2.75"
SMFZSDTR6036	60.1"	62.6"	36.5"	39"	2.75"
SMFZSDTR6332	64"	66.5"	32.5"	35"	2.75"
SMFZSDTR6336	64"	66.5"	36.5"	39"	2.75"









31 White	
32 Cameo	
40 Dark Grey	
09 Black	





Meets or Exceeds the Following Specification ASME A112.18.1 / CSA B125.125.1-11

- IGC 154-2012
 - cUPC® IAPMO

