

### FEATURES

- Round style diverting tub spout
- 5-1/2" long
- 1/2" NPT male thread connection
- Zinc material
- 6.01 gpm (22.74 L/min) @ 60 PSI (0.41 MPa)
- Additional noted flow rates:
  - 2.40 gpm (9.09 L/min) @ 10 PSI (0.07 MPa)
  - 3.42 gpm (12.93 L/min) @ 20 PSI (0.14 MPa)
  - 4.11 gpm (15.57 L/min) @ 30 PSI (0.2 MPa)
  - 4.81 gpm (18.21 L/min) @ 40 PSI (0.27 MPa)
  - 5.20 gpm (19.7 L/min) @ 45 PSI (0.31 MPa)
  - 5.53 gpm (20.95 L/min) @ 50 PSI (0.34 MPa)
  - 6.53 gpm (24.71 L/min) @ 70 PSI (0.48 MPa)
  - 7.01 gpm (26.54 L/min) @ 80 PSI (0.55 MPa)
- Lifetime Limited Residential / 1-Year Limited Commercial Warranty



### To Be Specified:

|                          | Model No. | Description         | Width   | Height  | Depth  |
|--------------------------|-----------|---------------------|---------|---------|--------|
| <input type="checkbox"/> | SMRTSD-   | Diverting Tub Spout | 2 7/16" | 2 7/16" | 5 1/2" |

### To Be Specified: Finish

|                          |    |                 |
|--------------------------|----|-----------------|
| <input type="checkbox"/> | PC | Polished Chrome |
| <input type="checkbox"/> | BN | Brushed Nickel  |
| <input type="checkbox"/> | MB | Matte Black     |



Polished Chrome



Brushed Nickel



Matte Black

