

STERLING®


A KOHLER COMPANY

ACCORD®

Features

- Compression molded from our exclusive solid Vikrell® material
- Modular 4-piece design
- Pivot "snap together" installation
- Caulkless seam installation
- Pre-attached grab bars constructed from anodized aluminum
- Convenient shelves provide generous storage
- Durable, chemical-resistant removable seat
- Removable seat can be conveniently placed on either side of shower base
- Not recommended as a shower base only installation
- 10-year consumer/3-year commercial limited warranty
- 48-1/8" (1222 mm) x 37-1/4" (946 mm) x 76" (1930 mm) rough-in dimensions include nailing flange
- 48" (1219 mm) x 36" (914 mm) x 74-1/2" (1892 mm) complete unit finished dimensions

48" SEATED SHOWER BASE AND SURROUND WITH GRAB BARS 72280103



Codes/Standards Applicable

Specified model meets or exceeds the following:

- ASTM E662
- CSA B45.5/IAPMO Z124
- ASTM E162

Colors/Finishes

- 0: White
- N: Nickel
- V: Matte Silver
- Other: Refer to Price Book for additional colors/finishes

Specified Model

Model	Complete Unit Description	Grab Bar Finishes			Fixture Colors	
72280103	48" seated shower base and surround with grab bars	<input type="checkbox"/> N	<input type="checkbox"/> V	<input type="checkbox"/> Other_____	<input type="checkbox"/> 0	<input type="checkbox"/> Other_____
Model	Component Description	Grab Bar Finishes			Colors/Finishes	
72281100	48" shower base with removable seat				<input type="checkbox"/> 0	<input type="checkbox"/> Other_____
72284103	48" complete wall set with grab bars	<input type="checkbox"/> N	<input type="checkbox"/> V	<input type="checkbox"/> Other_____	<input type="checkbox"/> 0	<input type="checkbox"/> Other_____

ACCORD®

Technical Information

Door maximum width		Door maximum height	
44-1/8" (1121 mm) at threshold		70-5/8" (1794 mm)	
44-5/8" (1133 mm) at top		(1794 mm)	
Removable seat	Height	Surface width	Surface length
	15-3/4" (400 mm)	11-3/4" (298 mm)	21-1/4" (540 mm)

Installation Notes

Install this product according to the installation guide.


Size the drain cutout to fit the drain assembly that will be used.

End stud positioning is critical.

Double studding is recommended for pivot shower door installations.

Studs should be positioned roughly as shown.

Shower base cannot be installed without the wall surround.



Product Diagram

ACCORD® 48" SEATED SHOWER BASE AND SURROUND WITH GRAB BARS