

Features

- Framed, 1/8" (3 mm) thick tempered glass.
- Continuous guide mechanism for smooth, quiet sliding action and easy cleaning.
- Reversible top track and towel bar offer multiple aesthetic options.

Material

- Anodized aluminum prevents rusting or corrosion.
- Tempered glass ensures maximum safety and durability.

Installation

- Out-of-plumb adjustability allows for simpler installation.
- Can be installed to open to the left or right.

Components

Additional included component/s: Hardware kit.

5905-59

Framed Sliding Bath Door

Deluxe

Codes/Standards

ANSI Z97.1 (Tempered Glass) CPSC 16CFR 1201

STERLING[®] Warranty - Bath and Shower Doors

See website for detailed warranty information.

Available Color/Finishes

Color tiles intended for reference only.

Color Code Description

Ν	Nickel
Ν	Nickel


- S Silver
- S Silver
- S Silver

Available Glass Options Code Description

Birchwood® Templar™







All product dimensions are nominal.Installation type:For bath installationOpening Width - Min:54-3/8" (1381 mm)Opening Width - Max:59-3/8" (1508 mm)Walk-through - Min:23-9/16" (599 mm)Walk-through - Max:28-9/16" (726 mm)Glass thickness:1/8" (3 mm)

Install this product according to the installation guide.

The vertical opening should be a minimum of 57-3/4" (1467 mm) to allow for installation clearance.