



**Accord®**  
60" x 30" ADA Bath  
**71141124**



### Features

- Durable high gloss finish.
- Above-floor-drain (AFD) rough-in.
- In-tub removable seat mounts directly to the back of the bath and rests on the apron.
- 17-1/4" (438 mm) bath depth (floor to top of threshold).
- 60" (1524 mm) x 30" (762 mm) complete unit finished dimensions.

### Material

- Compression molded from our exclusive Vikrell® material.

### Installation

- Bath only installation not recommended. Must be used with STERLING wall set.



**ADA** **CSA B651**

### Codes/Standards

CSA B45.5/IAPMO Z124  
ASTM E162  
ASTM E662  
Greenguard UL 2818 - Gold  
ADA  
ICC/ANSI A117.1  
CSA B651



**STERLING® Warranty - Fixtures Made of Solid Vikrell Material**

**STERLING® Warranty - Bathing & Showering Seats**

See website for detailed warranty information.

### Available Color/Finishes

*Color tiles intended for reference only.*

Color	Code	Description
	0	White
	96	KOHLER Biscuit

USA/Canada: 1-800-STERLING (1-800-783-7546)

Kohler Co. reserves the right to make revisions without notice to product specifications.

For the most current Specification Sheet, go to [www.sterlingplumbing.com](http://www.sterlingplumbing.com).

7-9-2016 03:03



**Accord®**  
60" x 30" ADA Bath  
**71141124**

No image available.

This product is a component and not intended to be a standalone installation.

### Technical Information

All product dimensions are nominal.

Installation:	3-Wall Alcove, Seated Alcove
Drain location:	Right
Basin area, bottom:	46-1/4" x 20-1/2" (1175 mm x 521 mm)
Basin area, top:	52-1/4" x 22-1/2" (1327 mm x 572 mm)
Water depth:	11" (279 mm)
Water capacity:	34 gal (128.7 L)
Door width required:	56-1/2" (1435 mm)

### Notes

Install this product according to the installation instructions.

Width of back wall at top transitions from 60" (1524 mm) at the front to 59-3/8" (1508 mm) in the back corners. Furring strips approximately 1/4" (6 mm) thick should be used at the back corner studs if drywall is to be installed over the nailing flange.

Studs should be positioned roughly as shown.

Double studding is recommended for pivot shower door installations.

Bath cannot be installed without the wall surround.

Product is designed to be used with a single-hole mixer valve with an escutcheon cover not to exceed 7-3/4" (197 mm) in width.

ADA, CSA B651 compliant when installed to the specific requirements of these regulations.