



**Accord®**

60" x 30" ADA smooth wall set w/grab bars  
**71244123**



### Features

- Solid Vikrell material
- Pivot snap-together modular design
- Smooth, high-gloss walls
- No caulk required
- Corner shelves; grab bars on back and right walls
- Must be installed with Accord bath (71141114 or 71141124)



**ADA**

### Codes/Standards

CSA B45.5/IAPMO Z124  
ASTM E162  
ASTM E662  
ADA  
ICC/ANSI A117.1



### Warranty – Bathing Fixtures (and) Kitchen and Utility Sinks Made of Solid Vikrell® Material

#### STERLING® Warranty - Grab Bars

See website for detailed warranty information.

### Available Colors/Finishes

*Color tiles intended for reference only.*

Color	Code	Description
	0	White
	96	KOHLER Biscuit

1-800-STERLING (1-800-783-7546)

Kohler Co. reserves the right to make revisions without notice to product specifications.

For the most current Specification Sheet, go to [www.sterlingplumbing.com](http://www.sterlingplumbing.com).

10-24-2019 06:14 - US



**Accord®**

60" x 30" ADA smooth wall set w/grab bars  
**71244123**

No image available.

This product is a component and not intended to be a standalone installation.

### Technical Information

All product dimensions are nominal.

Installation: Three-wall alcove  
Maximum door height: 55-7/8" (1419 mm)  
Maximum door width: 56-3/4" (1441 mm)

### Notes

Install this product according to the installation instructions.

Product is designed to be used with a single-hole mixer valve with an escutcheon cover not to exceed 7-3/4" (197 mm) in width.

Bath cannot be installed without the wall surround.

Width of back wall at top transitions from 60" (1524 mm) at the front to 59-3/8" (1508 mm) in the back corners. Furring strips approximately 1/4" (6 mm) thick should be used at the back corner studs if drywall is to be installed over the nailing flange.

ADA compliant when installed to the specific requirements of these regulations.