



# Lawson™

## 72" Whirlpool Bath with Heater

### 76301100-H



#### Features

- End drain.
- Durable high-gloss finish.
- 72" (1829 mm) x 36" (914 mm) x 20-5/16" (516 mm) unit rough-in dimensions include flanges.
- 72" (1829 mm) x 36" (914 mm) x 20-5/16" (516 mm) finished dimensions.

#### Material

- Compression-molded from our exclusive solid Vikrell® material.

#### Hydrotherapy

- Pump with air switch and grounding-type plug-in cord.
- Six fully-adjustable hydro-massage jets (color-matched and factory-installed).
- Includes heater.

#### Installation

- Drop-in or alcove installation.



#### Codes/Standards



ASME A112.19.7/CSA B45.10  
CSA B45.5/IAPMO Z124  
ASTM E162  
ASTM E662  
UL 1795  
CSA C22.2 No. 218.2  
Greenguard UL 2818 - Gold


#### STERLING® Warranty - Fixtures Made of Solid Vikrell Material

See website for detailed warranty information.

#### Available Color/Finishes

*Color tiles intended for reference only.*

Color	Code	Description
	0	White
	96	KOHLER Biscuit



### Required Electrical Service

Two dedicated circuits required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI) or Residual Current Device (RCD).

Pump: 120 V, 15 A, 60 Hz  
Heater: 120 V, 15 A, 60 Hz

### Technical Information

All product dimensions are nominal.

Installation: Drop-in, 3-Wall Alcove  
Drain location: End  
Basin area, bottom: 50-3/8" x 21-3/4" (1280 mm x 552 mm)  
Basin area, top: 58-1/4" x 27" (1480 mm x 686 mm)  
Weight: 103 lbs (46.7 kg)  
Water depth: 15-1/4" (387 mm)  
Water capacity: 68 gal (257.4 L)  
Electrical component rating: Pump: 120 V, 7 A, 60 Hz  
Heater: 120 V, 12.5 A, 60 Hz, 1500 W  
Pump speed: Single  
Minimum flat for door: 3" (76 mm)

### Notes

Install this product according to the installation instructions.

Provide one grounded electrical outlet within 24" (610 mm) of each component.

Measure your actual product for roughing-in details.

A pump motor/control access panel is required.

Size the drain cutout to fit the drain assembly that will be used.

End stud positioning is critical if nailing-in flanges are to be used.

Studs should be positioned roughly as shown for support clip or roofing nail installation.