

## Windham™ elongated toilet 402325

#### **Features**

- Two-piece design
- Elongated bowl offers added room and comfort
- Comfort Height® feature offers chair-height seating that makes sitting down and standing up easier for most adults
- 1.6 gpf (6.0 lpf)
- Left-hand Polished Chrome trip lever
- 2-1/8" (54 mm) fully glazed trapway
- Combination consists of 403317 bowl and 402363 tank
- Pro Force® Plus flushing technology delivers greater flushing power than previous Pro Force® models

#### Installation

- Three-bolt quick-connect installation
- Standard 12" (305 mm) rough-in
- Seat and supply line sold separately

#### **Recommended Products/Accessories**

K-20110 Brevia<sup>™</sup> Quiet-Close<sup>™</sup> elongated toilet seat K-9466-L Left-Hand Trip Lever K-5420 Low-Profile Bolt Caps K-23726 Drain treatment

#### **Included Components**

403317 Elongated chair height toilet bowl 402363 Toilet tank



ADA CSA B651 OBC

#### Codes/Standards

ASME A112.19.2/CSA B45.1 DOE - Energy Policy Act 1992 ADA ICC/ANSI A117.1 CSA B651 OBC IAPMO Certification

### STERLING® Toilet Limited Warranty

See website for detailed warranty information.

#### **Available Colors/Finishes**

Color tiles intended for reference only.


Color Code Description

0 White



# Windham™

elongated toilet 402325



### **Technical Information**

All product dimensions are nominal.

Toilet type: Floor-mount

Waste Outlet: Floor
Bowl shape: Elongated

Flush type: Gravity siphon jet
Trap passageway: 2-1/8" (54 mm)
Rough-in: 12" (305 mm)

**Notes** 

Install this product according to the installation instructions.

For back-to-back toilet installations: Use only a 45° double wye fitting.

ADA, OBC, CSA B651 compliant when installed to the specific requirements of these regulations.

Plumbing codes may require elongated toilets and elongated, open-front seats in public bathrooms.

Accessibility standards may require controls to be located on the open side of the toilet.