



OC-SS-39

39-3/8" x 39-3/8" Vikrell® shower with Aging in Place backerboards, center drain

62050106



Features

- 1/2" (12.7 mm) threshold
- Durable swirl-gloss finish
- Three-piece tongue-and-groove walls with snap-together installation
- Aging in Place backerboards

Material

- Made from solid Vikrell® material for strength, durability, and lasting beauty

Installation

- Alcove
- Center drain
- Caulk required for proper installation

Recommended Products/Accessories

K-23726 Drain treatment
K-23733 Vikrell® cleaner

Included Components

62055106 39-3/8" Vikrell® shower end wall set with Aging in Place backerboards
62051100 39-3/8" x 39-3/8" Vikrell® shower base, center drain
62052106 39-3/8" Vikrell® shower back wall with Aging in Place backerboards



Codes/Standards

CSA B45.5/IAPMO Z124
ASTM E162
ASTM E662
HUD, UM Bulletin 73


STERLING® Vikrell® or Acrylic Baths and Shower Bases Ten-Year Limited Warranty



See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.

Color Code Description

	0	White
---	---	-------



Note: Right end wall is the same as left end wall, only mirrored.
Backer board locations

Technical Information

All product dimensions are nominal.

Drain location: Center

Notes

Install this product according to the installation instructions.

Backerboards and fasteners protrude beyond the back wall 1-1/2" (38 mm). If installing this product against wall board, 1-1/2" (38 mm) furring strips installed over the wall board are recommended. The stud pocket depth of 40-5/8" (1032 mm) will need to be increased by the combined thickness of the wall board and furring strips.

1/2" minimum finished floor thickness required.

Studs should be positioned as shown.

Attach grab bars at the specified backerboard locations only.

Drain cutout in subfloor to be 10-1/2" (267 mm) per rough-in illustration as shown to allow the backside of the drain to sit below the subfloor surface.