

FINESSETM

Features

- CleanCoat™ glass coating
- · Heavy-duty, anodized aluminum-framed glass doors
- · Out-of-plumb adjustability allows for easy installation
- Top track roller system and continuous contact bottom track combine for a smooth, silent operation
- Aluminum components extruded from alloy 6063-T5
- Reversible top track can be installed with either the round or flat side facing out
- Stainless steel hardware prevents rusting or corrosion
- 1/4" (6 mm) thick tempered glass
- Two through-the-glass towel bars, located both inside and outside, enhance appearance and usability

Codes/Standards Applicable

Specified model meets or exceeds the following:

• ANSI Z97.1 (tempered glass)

FRAMELESS BYPASS BATH/ SHOWER DOOR 5405 ALSO 5425, 5475



Colors/Finishes

- S: Silver
- PB: Polished Brass
- N: Nickel
- DR: Deep Bronze

Specified Model

Model	Application	Glass Texture	Pattern	* Frame	* Frame Colors/Finishes		
5405-59*-G05	Bath	Smooth	Clear	□S	□ PB	□N	□ DR
5405-59*-G57	Bath	SolsticeTM	None	□S		□N	□ DR
5425-57*-G05	Bath	Smooth	Clear	□S	□ PB		□ DR
5425-59*-G05	Bath	Smooth	Clear	□S	□ PB	□N	□ DR
5425-59*-G57	Bath	Solstice™	None	□S		□N	□ DR
5475-48*-G05	Shower	Smooth	Clear	□S	□ PB	□N	□ DR
5475-48*-G57	Shower	Solstice™	None	□S		□N	□ DR
5475-59*-G05	Shower	Smooth	Clear	□S	□ PB	□N	□ DR
5475-59*-G57	Shower	SolsticeTM	None	□S		□N	□ DR

Technical Information

Model	A (max width)	B (height)	C (walk through max)
5405-59	59-5/8" (151.4 cm)	58-1/16" (147.5 cm)	27-7/8" (70.8 cm)
5425-57	57" (144.8 cm)	55-1/2" (141 cm)	26-5/8" (67.6 cm)
5425-59	59-5/8" (151.4 cm)	55-1/2" (141 cm)	27-7/8" (70.8 cm)
5475-48	47-5/8" (121 cm)	70-1/16" (178 cm)	21-7/8" (55.6 cm)
5475-59	59-5/8" (151.4cm)	70-1/16" (178 cm)	27-7/8" (70.8 cm)



