

US-3015 Swanstone Undermount Double Bowl Kitchen Sink

Manufactured from Swanstone solid surface

Recommended for high-use traffic areas and commercial surfaces.

(See page 2 for detailed information.)


WARRANTY


Limited Lifetime - Residential

Limited 10-year - Commercial

FEATURES

- Reinforced solid surface means color and texture run all the way through and cannot wear away.
- Mounts underneath your choice of countertop for high-design appeal.
- Heat and stain, resistant for lasting beauty.





Capacity: 6 gallons in large (left) bowl, 5-1/2 gallons in small (right) bowl

SPECIFICATIONS

US-3015 Swanstone Double Bowl Kitchen Sink

Model	Part	Nominal Dimensions	Ship Wt. Lb.	Ship FedEx	Carton Dims. In.	Cu. Ft.
US-3015	US03015SB	32-3/4" W x 21-1/8" D (832 mm x 539 mm)	39	FedEx	37 X 24 X 13	6.68

COLORS

Solid Colors:

- White (010)
- Bisque (018)
- Bone (037)

Aggregate Colors:

- Acorn (123) 🔊
- Arctic Granite (035)
- Baby's Breath (168)
- Barley (091)
- Bermuda Sand (040)
- Black Galaxy (015)
- Canyon (124) 🗖
- Caraway Seed (169)

- Glacier (121) 🗖
- Gray Granite (042)
- Night Sky (012)
- Pebble (072)
- Prairie (122) 💋
- Tahiti Desert (050)
- Tahiti Gray (053)
- Tahiti Ivory (059)
- Tahiti Matrix (058)
- Tahiti Sand (051)
- Tahiti White (011)
- Our Planet Colors

STANDARDS AND RATINGS

American National Standard Institute—ANSI Z124.6

International Association of Plumbing and Mechanical Officials (IAPMO)—Listed cUPC listed—Certified to CSA Test Standard B45.5 by IAPMO Uniform Plumbing Code (UPC)

National Sanitation Foundation-NSF/ANSI 51 Food Equipment Materials

For a complete list of tests and results see the Technical Data Sheet.

SUPPORT DOCUMENTS

Installation instructions available at swanstone.com.

MAINTENANCE AND CLEANING INFORMATION

Clean your Swanstone sink by using abrasive cleaners or other similar products. Use of a nylon scouring pad or Mr. Clean® Magic Eraser® is also recommended. Food-based stains can be removed using a 50-50 mix of bleach and water solution and soaking for 15 minutes. For rust or other mineral stains, rust-removing products are acceptable. **Do not** use metal scouring pads.

