



SYMMONS® Euro-Flo™

Location:



H401-V

5 Mode Hand Shower Unit

Specification Submittal

Model Numbers

☐ **H401-V** Hand Shower

Options/ Modifications

- ☐ **1.5**  **1.5 gpm (5.7 L/min) flow restrictor**
- ☐ **STN** **Satin Nickel finish**
- ☐ **72** **72" hose in place of 60" hose**
- ☐ **L2** **Less hand shower wand**

Note: Append appropriate -suffix to model number.

Compliance

- ASME A112.18.1/CSA B125.1



Feature Highlights

- Euro-Flo™ single function hand shower with full drenching spray head
- 5 foot flexible metal hose with in-line vacuum breaker, wall connection, cradle and flange
- Standard flow rate at 2.0 gpm (7.6 L/Min)
- Optional aerator available in lower flow rates
- Polished chrome finish
- For optional in-line vacuum breaker order p/n EF-109

Warranty

Limited Lifetime - to the original end purchaser in consumer/residential installations.

10 Years - for commercial/industrial installations. Refer to www.symmons.com/warranty for complete warranty information.



Architectural/ Engineering Specification

Symmons Euro-Flo 5 Mode Hand Shower Unit _____ Includes Euro-Flo single function hand shower with full drenching spray head, 5 foot flexible metal hose with in-line vacuum breaker, wall connection, cradle and flange, Standard flow rate at 2.0 gpm (7.6 L/Min), Optional aerator available in lower flow rates, Polished chrome finish, For optional in-line vacuum breaker order p/n EF-109. 10 Year Commercial Warranty. ASME A112.18.1/CSA B125.1 compliant. Available options: "1.5 - 1.5 gpm (5.7 L/min) flow restrictor", "STN - Satin Nickel finish", "72 - 72" hose in place of 60" hose", "L2 - Less hand shower wand".