

Specification & Submittal Form 91111N Caregiver Door

ARC, Inc. I-877-319-6521 info@arcfirst.net

I. General Description

a. A low height shower door that eases shower entry and exit, improves privacy and warmth for bather, permits caregiver access, and protects caregiver from overspray.

2. Item Codes and Descriptions

a. 91111N . . . Alcove caregiver door

3. Physical Characteristics

- a. Door height: 291/2"
- b. Door width: fits alcoves 503/4" to 513/4" wide with supplied compensators
- c. Two compensators are supplied with each caregiver door model
- d. Up to 4" greater width may be achieved with the use of extra-wide compensators
 - i. 2" additional width with each extra-wide compensator
 - ii. each extra-wide compensator replaces an original compensators
 - iii. installer may use any combination of original and extra-wide compensators
- a. Compensators mount to the walls, and doors are secured into the compensators
- b. Aluminum frames with PET plastic panels
- c. PET panels are embossed with a surface texture
- d. PET plastic panels will not shatter
- e. A magnetic strip is installed at the unhinged edge of each door
- f. Each door segment has an elastomeric gasket that contacts the floor
- g. Hinges and caps are made of nylon 6
- h. Bi-fold doors swing 180° in and out, and fold against each other
- i. Handles pivot to unlock or lock adjacent door segments
- j. Color
 - i. frames: white
 - ii. corners: gray
 - iii. compensators: white
 - iv. compensator caps: gray
 - v. handles: white
 - vi. elastomeric gaskets: gray
- k. Fasteners not included

4. Performance Characteristics

- a. For Mullen and wet room installations
- b. No rust construction
- c. Door swing allows generous access
- d. Pattern on PET panels provides privacy
- e. Magnetic strips and gaskets increase water retention
- f. Handles are designed to give way to the force of a fall against the doors, thus limiting injury to the user and damage to the doors (replacement handles are available)
- Compensators allow for adjustments in overall fit, sizing the doors for width, and ensuring a plumb installation

5. Other Information

- a. 5 year limited warranty when installed in commercial settings
- b. 10 year limited warranty when installed in residential settings
- c. See AKW warranty for details

