

# Specification & Submittal Form 91112N Caregiver Door

ARC, Inc. I-877-319-6521 info@arcfirst.net

# I. General Description

a. A low height shower door that eases shower entry and exit, improves privacy and warmth for bather, permits caregiver access, and protects caregiver from overspray.

## 2. Item Codes and Descriptions

a. 91112N . . . Alcove caregiver door

# 3. Physical Characteristics

- a. Door height: 291/2"
- b. Door width: fits alcoves 541/2" to 551/2" wide with supplied compensators
- c. Two compensators are supplied with each caregiver door model
- d. Up to 4" greater width may be achieved with the use of extra-wide compensators
  - i. 2" additional width with each extra-wide compensator
  - ii. each extra-wide compensator replaces an original compensators
  - iii. installer may use any combination of original and extra-wide compensators
- a. Compensators mount to the walls, and doors are secured into the compensators
- b. Aluminum frames with PET plastic panels
- c. PET panels are embossed with a surface texture
- d. PET plastic panels will not shatter
- e. A magnetic strip is installed at the unhinged edge of each door
- f. Each door segment has an elastomeric gasket that contacts the floor
- g. Hinges and caps are made of nylon 6
- h. Bi-fold doors swing 180° in and out, and fold against each other
- i. Handles pivot to unlock or lock adjacent door segments
- j. Color
  - i. frames: white
  - ii. corners: gray
  - iii. compensators: white
  - iv. compensator caps: gray
  - v. handles: white
  - vi. elastomeric gaskets: gray
- k. Fasteners not included

## 4. Performance Characteristics

- a. For wet room installations only
- b. No rust construction
- c. Door swing allows generous access
- d. Pattern on PET panels provides privacy
- e. Magnetic strips and gaskets increase water retention
- f. Handles are designed to give way to the force of a fall against the doors, thus limiting injury to the user and damage to the doors (replacement handles are available)
- Compensators allow for adjustments in overall fit, sizing the doors for width, and ensuring a plumb installation

#### 5. Other Information

- a. 5 year limited warranty when installed in commercial settings
- b. 10 year limited warranty when installed in residential settings
- c. See AKW warranty for details

