

FEATURES


- Single threshold for alcove installation.
- Heavy duty integral 1" high tiling flange for a waterproof installation.
- 3" wide threshold as well as a 3" threshold height for a modern design.
- Designed for installation for new or existing construction.
- Easy installation. Level with thinset mortar mix.
- 10 Year Limited Residential Warranty / 3 Year Commercial Warranty.

FL Classic Shower Base

- SMC sheet molding compound material is made from a composite material composed of resin, fiberglass, and stone filler. Compression molded solid surface for a precise radius and angles. It is strong, lightweight, slip resistant and scratch resistant.
- Features a stainless steel concealed drain removable cover that brings both a design element and comfort to your shower experience. Lift-off cover allows for easy cleaning. ABS drain is included.






Modern Slip Resistance with a light rectangular comfortable texture. Easy to clean as well as slip resistant.




Specified Model

FL Center Drain Shower Bases											
	Model	A	B	C	D	E	F	G	H	I	Wt.
<input type="checkbox"/>	FL6036C	36"	18.9"	17.1"	30"	60"	60"	59.8"	33"	36"	72
<input type="checkbox"/>	FL6034C	34"	17.9"	16.1"	30"	60"	60"	59.8"	31"	34"	67
<input type="checkbox"/>	FL6032C	32"	16.9"	15.1"	30"	60"	60"	59.8"	29"	32"	62
<input type="checkbox"/>	FL4836C	36"	18.9"	17.1"	24"	48"	48"	47.8"	33"	36"	52
<input type="checkbox"/>	FL4832C	32"	16.9"	15.1"	24"	48"	48"	47.8"	29"	32"	47

To Be Specified: Color

<input type="checkbox"/>	31 White			
<input type="checkbox"/>	32 Cameo	White 31	Cameo 32	Grey 39
<input type="checkbox"/>	39 Grey			

Compliance Certifications - Meets or Exceeds the Following Specifications

- IGC 154-2012
- ASME A112.18.1 / CSA B125.125.1-11
- ASTM 1028-96 coefficient of friction test (minimum rating of 0.67)
- IAPMO 
- cUPC®

FL Classic Linear Base

