

# Specification & Submittal Form Freestanding Glass Screen

ARC, Inc. I-877-319-6521 info@arcfirst.net

### I. General Description

 Tempered glass panel captured by aluminum posts for use as a shower screen.

# 2. Item Codes and Descriptions

a. LB00112 . . . 39%"-wide freestanding glass screen

# 3. Physical Characteristics

- a. Screen height: 763/4"
- b. Glass thickness: 6mm (about 1/4")
- c. Glass type: tempered
- d. Includes end posts, post caps, foot assemblies, two tie bar assemblies, and one bottom seal
- e. Posts and tie bar assemblies are polished aluminum
- f. Post caps, foot assemblies, and escutcheons are plastic
- g. Bottom seal is flexible plastic
- h. Non-handed
- i. Screens allow a gap to floor of about 3/8"
- j. Posts are pre-installed onto screen
- k. Tie bar length: 55"
- I. Fasteners not included

# 4. Performance Characteristics

- a. Tempered glass increases safety
- b. Aluminum parts will not rust
- c. Gap to floor may be filled with bottom seal if desired
- d. Foot assemblies offer adjustability to level and plumb screen
- e. Cover foot assemblies with decorative escutcheons
- f. Tie bars must be installed. They may be used to connect a screen to a wall or connect one screen to others
- g. Bottom seal may be cut to desired length
- h. Tie bars may be cut to desired length
- i. Tie bars attach to top end of posts

#### 5. Other Information

- a. 5 year limited warranty when installed in commercial settings
- b. 10 year limited warranty when installed in residential settings
- c. See AKW warranty for details



