

Features

- · Solid brass body
- · Ceramic disc cartridge
- Single lever handle
- 180 degree swivel spout
- Installation in a 1-3/8" hole
- 1-1/2" maximum deck thickness
- High arc spout with pull-out spray head
- Dual function ABS pull-out spray head aerated stream or spray
- 1.8 gpm max. (6.8L/min) @ 60psi saves 20% more water
- Flexible supply lines with 3/8" compression fittings

Optional Accessories

• T3600, T3610 or T3620 soap dispenser.

Warranty

- · Lifetime Limited Warranty for residential use
- 5 Year Limited Warranty for commercial use



22mm [55/64′

200mm

<u>[7 7/8″</u>]

Single Lever Pull-Out Spray

KENT T3650

Specified Model

Model	T3650
Faucet Height	15 ²⁹ / ₃₂ " (404 mm)
Spout Reach	71/8" (200 mm)
Deck to Aerator	8 ¹⁷ ⁄ ₆₄ " (210 mm)
Flow Rate	1.8 gpm max (6.8L/min) @ 60 psi
Shipping Weight	9 lbs.
Material	brass construction
Installation	deck mount, single hole

To Be Specified:

Finish	
PC Polished Chrome	
LS Luxe Stainless	
MB Matte Black	



Codes/Standards

Certified to CUPC Certified to AB1953 Certified to NSF/ANSI 61 Complies with Federal Lead Plumbing Law as certified with IAMPO R&T inc. ADA complaint for lever handle



Notes

Install this product according to the installation instructions.

0

Same

,5mm /64

108,5 ____/

1-1/2' MAX 40r 42mm

[1 21/32"]

ב"לצי