

Specification & Submittal Form Wall Mounted Glass Screens

ARC, Inc. I-877-319-6521 info@arcfirst.net

I. General Description

a. Tempered glass panel captured by aluminum posts and a wall-mounted compensator for use as a shower screen.

2. Item Codes and Descriptions

a. LB00105 . . . 271/2"-wide wall mounted glass screen

b. LB00106 . . . 311/2"-wide wall mounted glass screen

c. LB00107 . . . 351/2"-wide wall mounted glass screen

d. LB00108 . . . 393/8"-wide wall mounted glass screen

3. Physical Characteristics

- a. Screen height: 763/4"
- b. Glass thickness: 6mm (about 1/4")
- c. Glass type: tempered
- d. Includes compensator channel, wall post and external post, post caps, foot assemblies, one tie bar assembly, and one bottom seal
- e. Compensator, posts, and tie bar assembly are polished aluminum
- f. Post caps, foot assemblies, and escutcheons are plastic
- g. Bottom seal is flexible plastic
- h. Non-handed
- i. Screens allow a gap to floor of about 3/8"
- j. Tie bar length: 55"
- k. Posts are pre-installed onto screen
- I. Fasteners not included

4. Performance Characteristics

- a. Tempered glass increases safety
- b. Aluminum parts will not rust
- c. These models must be mounted at one end to a wall
- d. Compensator allows for adjustments to install screen plumb
- e. Gap to floor may be filled with bottom seal if desired
- f. Foot assemblies offer adjustability to level and plumb screen
- g. Cover foot assemblies with decorative escutcheons
- h. Tie bar must be installed from the screen to a wall
- Accessory tie bars are available to brace between glass screens
- j. Compensator may be cut to desired length
- k. Bottom seal may be cut to desired length
- I. Tie bars may be cut to desired length
- m. Tie bar assembly attaches to top end of external post
- n. External post can accommodate two tie rod connections

5. Other Information

- a. 5 year limited warranty when installed in commercial settings
- b. 10 year limited warranty when installed in residential settings
- c. See AKW warranty for details











