

Specification & Submittal Form Newel Grab Bars

ARC, Inc. I-877-319-6521 info@arcfirst.net

- I. General Descriptiona. Hand hold device for newel posts and corners
- 2. Item Codes and Descriptions
 - a. 01745L . . . Newel grab bar
 - a. 01745R . . . Newel grab bar
- 3. Physical Characteristics
 - a. Available in left and right handed models (left shown)
 - b. Made of cold drawn mild steel tube
 - c. Protected with epoxy resin coating
 - d. Finishing process includes rust inhibitor treatment
 - e. Grip diameter: I¹/₄"
 - f. Distance from grab bar to wall: $2^{1}/4^{"}$
 - g. Color: ivory
 - h. 3 mounting holes at each end
 - i. Mounting flanges are offset from grip area
 - j. 275 lb. load rating when properly fastened
 - k. Fasteners not included
 - I. Use of #10 round head fasteners recommended (use stainless fasteners for wet area installations)
- 4. Performance Characteristics
 - a. For installation on newel posts and corners
 - b. User can maintain grip throughout stairway entrance and exit, or while moving past a corner or through an archway
 - c. For indoor use
 - d. Must be fastened to properly installed wood blocking, studs, or other substantial material
- 5. Other Information
 - a. Conforms to 96 hour salt spray test (ASTM B117-87)
 - b. 10 year limited warranty for residential use
 - c. 5 year limited warranty for commercial use

